

SYNTHETIC RESINS - PAINT AND VARNISH / Solvent Based

IZELKYD MO 51WX55

PRODUCT DESCRIPTION

Solvent based, medium oil and oxidative drying alkyd resin High yellowing resistance High colour durability and gloss retention

TECHNICAL DATA SHEET

MEDIUM OIL ALKYD RESIN

STORAGE & SHELF LIFE

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature between 5-30 °C Exposure to direct sunlight should be avoided. The shelf life of the resin under the mentioned storage conditions is 1 year.

COMPATIBILITY

Long and medium oil alkyd resins

Compatible

DELIVERY FORM

IBC - 900 kg Barrel - 185 kg Bulk

APPLICATION

MATERIAL SAFETY

SDS for this product is available on request

Auto repair Industrial paints and varnishes Road marking Synthetic paints and varnishes

TECHNICAL SPECIFICATIONS

Property	Value	Unit	Test Method
Modification	Specific	-	-
Type of oil	TOFA	-	-
Oil percentage	51	%	-
Solvent type	White spirit / Xylene	-	-
Solid content	54-56	%	TS EN ISO 3251
Viscosity (Gardner 25 °C, %55 Solid)	Y-Z2 / 26,8-53,1	Gardner/sec	ASTM D 1545-13
Acid value	Max 12	mg KOH/g	TS 2366 EN ISO 2114
Density (20 °C)	0,93-0,96	gr/cm ³	TS EN ISO 2811-1
Colour (% 50 Solid)	Max 5	Gardner	TS EN ISO 4630

SOLUBILITY		RECOMMENDED DRYER RATES	
Acetone	Soluble	Cobalt	0,04-0,06 %
White spirit	Soluble	Zirconium	0,25-0,45 %
Toluene	Soluble	Calcium	0,15-0,35 %
Xylene	Soluble	Recommended scatter rates over 100% solid alkyd metal percentages.	

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet

IZEL KIMYA SAN. Ve TIC. A.Ş. Gebkim V (Kimya) Organize Sanayi Bölgesi İbrahim Başaran Caddesi No. 9 Dilovası / KOCAELİ Phone: +90 262 754 22 33 (pbx) Fax: +90 262 754 11 99 www.izelkimya.com.tr