

**SYNTHETIC RESINS - PAINT AND VARNISH / Solvent Based** 

# **RAPID (CHAIN-STOPPED) ALKYD RESIN**

## **IZELKYD RAP 25TX70**

### **PRODUCT DESCRIPTION**

Solvent based, short oil and oxidative drying alkyd resin High yellowing resistance High colour durability and gloss retention

### **STORAGE & SHELF LIFE**

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature between 5-30 °C Exposure to direct sunlight should be avoided. The shelf life of the resin under the mentioned storage conditions is 1 year.

#### COMPATIBILITY

Long oil alkyd resinsIncompatibleAmino resinsCompatibleShort oil alkyd resinsCompatibleCellulose nitrateCompatibleAromatic polyisocyanateCompatible

#### **DELIVERY FORM**

**MATERIAL SAFETY** 

SDS for this product is available on request

IBC - 1000 kg

Barrel - 200 kg

Bulk

#### **APPLICATION**

Auto repair
Industrial paints and varnishes
Floor paint
Anti corrosive paint
Hammerton paints

## **TECHNICAL SPECIFICATIONS**

Property	Value	Unit	Test Method
Modification	Specific	-	-
Type of oil	Soybean oil	-	-
Oil percentage	25	%	-
Solvent type	Toluene / Xylene	-	-
Solid content	69-71	%	TS EN ISO 3251
Viscosity (Gardner 25 °C)	Z4-Z5 / 93-144,5	Gardner/sec	ASTM D 1545-13
Viscosity (60%, Gardner 25 °C)	W-Y / 15,7-26,8	Gardner/sec	ASTM D 1545-13
Acid value	Max 10	mg KOH/g	TS 2366 EN ISO 2114
Density (20 °C)	1,04-1,08	gr/cm <sup>3</sup>	TS EN ISO 2811-1
Colour (%50 Solid)	Max 6	Gardner	TS EN ISO 4630

#### **SOLUBILITY**

Xylene

## **RECOMMENDED DRYER RATES**

Acetone	Soluble	Cobalt	0,03-0,06 %
White spirit	Insoluble	Zirconium	0,15-0,30 %
Toluene	Soluble	Calcium	0,10-0,20 %

Terebentine Insoluble

Soluble

Recommended scatter rates over 100% solid alkyd metal percentages.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet

www.izelkimya.com.tr