

**SYNTHETIC RESINS - PAINT AND VARNISH / Solvent Based** 

# **IZELKYD URAL O 68W60**

#### **PRODUCT DESCRIPTION**

TDI modified solvent based oxidative drying alkyd resin High yellowing resistance High colour durability and gloss retention

# **TECHNICAL DATA SHEET**

#### URETHANE ALKYD RESIN

#### **STORAGE & SHELF LIFE**

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature between 5-30 °C Exposure to direct sunlight should be avoided. The shelf life of the resin under the mentioned storage conditions is 1 year.

**DELIVERY FORM** 

#### COMPATIBILITY

Long oil alkyd resins Short oil alkyd resins Amino resins Compatible Incompatible Compatible

## IBC - 900 kg Barrel - 185 kg Bulk

#### APPLICATION

Parquet varnishes Marine paints and varnishes Wood Anti corrosive paint Industrial paints and varnishes

#### **MATERIAL SAFETY** SDS for this product is available on request.

### **TECHNICAL SPECIFICATIONS**

Property	Value	Unit	Test Method
Modification	TDI	-	-
Type of oil	Soybean oil	-	-
Oil percentage	68	%	-
Solvent type	White spirit	-	-
Solid content	59-61	%	TS EN ISO 3251
Viscosity (Gardner 25 °C)	X-Z1 / 18,9-39,6	Gardner/sec	ASTM D 1545-13
Acid value	Max 3	mg KOH/g	TS 2366 EN ISO 2114
Density (20 °C)	0,91-0,95	gr/cm <sup>3</sup>	TS EN ISO 2811-1
Colour (%50 Solid)	Max 7	Gardner	TS EN ISO 4630

SOLUBILITY		<b>RECOMMENDED DRYER RATES</b>	
Acetone	Soluble	Cobalt	0,04-0,06 %
White spirit	Soluble	Zirconium	0,25-0,45 %
Toluene	Soluble	Calcium	0,15-0,35 %
Xylene	Soluble	Recommended scatter rates over 100% solid alkyd metal percentages.	

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet

IZEL KIMYA SAN. Ve TIC. A.Ş. Gebkim V (Kimya) Organize Sanayi Bölgesi İbrahim Başaran Caddesi No. 9 Dilovası / KOCAELİ Phone: +90 262 754 22 33 (pbx) Fax: +90 262 754 11 99

www.izelkimya.com.tr